

FW9307-GPM

5MP Global Shutter ANPR/LPR

FW9307-GPM is Outdoor IR All-in-one Motorized Camera which is equipped with 5.07MP Global Shutter CMOS image Sensor. with the highest sensitivity sensor, it is especially superior in low light condition. As it supports simultaneous H.265, H.264 and MJPEG Video Compression, less network bandwidth and storage space required. It also delivers high quality video image at 15fps @ 5MP (2432x2048) or 30fps @ 4MP (2304x1728) in progressive mode.

Key Features



- Ambarella platform – Backdoor Issue free
- 2/3" 5.07MP Sony IMX264 Global Shutter CMOS sensor
- Strobe driven power LED (16EA)
- Good for ANPR or LPR
- 12.0~40.0mm Motorized Auto-Focus IR correction Lens (option 6.0~22.0mm)
- Quadruple Stream (H.265, H.264, M-JPEG, JPEG)
- Max. 15fps @ 5MP (2432x2048) or 30fps @ 4MP (2304x1728)
- Various Back light mode of WDR, BLC, HLC
- Night Color Level adjustment (Off, 10 steps)
- Shutter limit (Min./Max.) setting
 - Good for the better night time moving object image
 - To avoid saturation under strong back light or IR reflection
- OnVIF (Profile S) standardss
- FW9307-GPM 16 LED on main unit
- FW9307-GPM-E External 32 LED on left/right(Total 64 LED)



FW9307-GPM



FW9307-GPM-E



Tech Notes

Global shutter cameras for LPR

High-speed, smear-free still image capture is the hallmark of global shutter image sensors. Applications such as traffic management, metrology and robotics inspection all need to image fast-moving objects without smear or distortion. These imagers have the ability to electronically shutter itself and "stop the action."

Strobe Light

Strobes produce a bright light in a similar way to on-camera flash. They differ in that they're brighter, they produce extremely short bursts of light, and they recharge quickly.

FW9307-GPM

Technical Specifications

Camera	
Imaging Sensor	2/3" 5.07MP Sony IMX264 Global Shutter CMOS
Lens	12.0~40.0mm Motorized Auto-Focus(option 6.0~22.0mm)
Day & Night	True Day & Night (ICR)
Min. Illumination	Color : 0.05lux (0.02 lux DSS ON), B&W : 0 lux (IR On)
Video Stream	
System	Ambarella 32bit Embedded Linux 256Mbyte SDRAM, 128Mbyte NAND Flash
Compression	H.265, H.264, M-JPEG, JPEG
Resolution	2432x2048, 2304x1728, 2048x1536, 1920x1080, 1280x720, 704x480, 640x352, 320x176, 160x96
Frame rate	Max. 15fps @ 5MP Max. 30fps/25fps @ 4MP
Video Stream	Quadruple Streaming, selectable : H.265/H.264/MJPEG, Frame rate, Bitrate, VBR/AVBR/CBR/ACBR, GOP
Video Setting	
Motion Detection	4 Areas
Audio Detection	Enable (sensitivity setting) / Disable
Privacy Masking	8 Areas
Video Analytics	Optional (Face Detection, Tampering, Tripwire etc.)
Smart Video	ROI
Lens Type	ELC/ALC
AF Mode	Auto / Manual
Day-Night Auto Focus	OFF / ON
Brightness (Target Exposure Weight)	0~20
Shutter	Auto / Manual / Flicker
Auto Shutter Speed Min./Max. Setting	1/30~30,000 Shutter Auto, Lens ELC Deblur Mode
Max. AGC gain	0~10
Sense Up Level	OFF / x2 / x4 / x8 / x16 / x32
Strobe Timig Adjustment	-250~250
Back Light Mode	OFF / HLC / BLC / WDR
WDR Weight	Low / Middle / High
Image Adjustment	Sharpness, Gamma
White Balance	Auto / Preset / Manual
DNR	Off / Low / Middle / High
Day & Night Control	Auto / Color / B&W / External
Night Color Mode	Off / 1~10 10steps
Image Direction	Mirror(On/Off), Flip(On/Off)
Advanced Image Adjustment	Defog, D-Zoom, D-WDR, Shading, EIS(DIS)
Network	
Security	IP Filtering, HTTPS, Encrypted & Basic Authentication, Management White List

Supported protocols	HTTP, RTP/RTSP(Uni/Multicast), TCP/IP(v4/v6), UDP, FTP, Telnet, HTTPS, RARP, SNMP, DHCP, NTP, SMTP client, uPnP&etc
DDNS	www.ipcctvdns.com
Interface	RJ45 Ethernet 10/100Mbps
System Integration	
Programing Interface	SDK, OnVIF Profile S
Video Analytic	Motion detection. Optional: ROI, Tripwire, Tampering, Face Detection
Triggering Event	Motion detection, triggering DI, triggering serial input, connected/disconnected, boot finished
Action on Event	Pre-alarm & Post-alarm buffer. Upload FTP, Email notification, FCM Google notification
Connection	1 DI/ 1DO, RS485
Illuminator	
Type	FW9307-GPM(16EA on main unit) FW9307-GPM-E(32 x 32, 64EA)
Onboard storage	
Type	1 MicroSD Slot
Recording	Always, Schedule, Event, Schedule & Event
Playback	Internet Explorer, FlexWATCH NVR/ CMS/ Mobile App
Audio	
Compression	8bit G.711, 8Khz, 8KByte/sec
Audio stream	2 way
Connection	Optional, 1 Audio In / 1 Audio Out
General	
Case	Metal
Power Supply	AC 110~220V free voltage
Power Consumption	FW9307-GPM 150mA/7.2W @ 1/500 75mA/3.6W @ 1/1000 25mA/1.2W @ 1/2000 FW9307-GPM-E 600mA/28.8W @ 1/500 300mA/14.4W @ 1/1000 100mA/4.8W @ 1/2000
Operating Environment	-20°C ~ +60°C, 10% ~ 90% RH
Dimension	152(W) x 395(D) x 116(H) mm (With sunshield)
Weight	FW9307-GPM About 1950g FW9307-GPM-E About 3600g
Approval	KC, CE, RoHS, IP66, IK10
Accessories	-
Bundle Software	IP Installer, SMVP, Smart NVR Lite